

Patriot Line of Utility Work Boats (no Cabin)

Model Standard Specifications Model P-2070

Length Overall:	20 ft.
Beam Overall:	7 ft. 0 in.
Standard Fuel Capacity:	Optional
Maximum O/B Horsepower:	200

Propulsion

- Outboard
- Gasoline

Single or twin outboard motors can be transom or bracket mounted.

Standard Equipment

- All Aluminum
- Available in 5086 and 5052 alloy plate
- Hydraulic steering center console or side consol
- Adjustable operator's seat
- Navigation lights
- 12 volt DC electrical system w/ 8 circuit switch panel
- 2000 GPH electric bilge pump w/ auto-manual control
- Mooring bitts (4)
- 4 in. Heavy Duty Rubber Bumper
- Safety Rail
- Bow tow eye
- 5 lb. Sacrificial anodes (2)
- Safety non-skid decks and wide diamond plate gunnels
- Custom Fuel tanks
- Lifting eyes
- Push Knees
- Outboard protection bar (motor guard)
- Bench Seats with Storage
- Horn

Any of the Patriot Line of Utility Work Boats can be customized to meet any requirements. Boats can be manufactured in lengths from 20' to 54'. Click on the model number below for additional specifications, features, and options:

Model	Length Overall	Beam Overall
P-1770	17 ft.	7 ft. 0 in
P-2070	20 ft.	7 ft. 0 in.
P-2280	22 ft.	8 ft. 0 in.
P-2484	24 ft.	8 ft. 4 in.
P-2680	26 ft.	8 ft. 4 in.
P-2884	28 ft.	8 ft. 5 in.

Model A-2070 Construction Details

Bottom Plating: 1/4 in.

Side Plating: 3/16 in.

Deck Plating: 3/16 in.

Cockpit Plating: 3/16 in.

Transom Plating: 1/4 in.

Options

- Navigation and communication equipment
- Lifting davits/A-frame boom
- Flood lights/Docking lights
- Diving platform
- Safety equipment
- Towing bitt or frame
- Emergency lights
- Generators
- Air Conditioning/Heating Strip
- Radar
- VHF Radio
- Depth Sounder
- Custom Transducer Launcher
- Bow load ramp (electric or manual)
- Motor Gill Bracket
- Custom Handrails
- Bottom Anti-foulant Coating
- Many other options available